

KSF02-63-3P



KSF02-32-1P+N

SYMBOL	INDEX / INDEKS	POLES BIEGUNY	PACKAGING / PAKOWANIE
KSF02-32-1P+N	23340	1P + N	-/3/36
KSF02-63-1P	23341	1P	-/6/72
KSF02-63-1P+N	23342	1P + N	-/3/36
KSF02-63-3P	23343	3P	-/2/24
KFB02-63-1P	23344	1P	-/20/200



EN

Fuse switch disconnecter KSF D02 is an apparatus which allow to exchange fuse link protecting electrical circuits for fuse links of D02, max In 63A, 240/415 AC.
According to standard: EN6047-3.

PL

Rozłącznik izolacyjny z bezpiecznikiem KSF D02 jest aparatem który umożliwia wymianę wkładki topikowej zabezpieczającej instalacje elektryczne na bezpieczniki systemu D02, maksymalny prąd znamionowy 63 A, 240/415 V AC.
Zgodność z normą: EN6047-3.




KFL-D02

Fuse link D02
Bezpiecznik topikowy D02



DIMENSIONS (mm) / WYMIARY (mm)			
SYMBOL	øA	øB	L
KFL-D02-20	10,9	15	36
KFL-D02-25	12,1	15	36
KFL-D02-35	13,3	15	36
KFL-D02-50	14,5	15	36
KFL-D02-63	15,9	15	36



KFL-D02

SYMBOL	INDEX / INDEKS	NOMINAL CURRENT In PRĄD ZNAMIONOWY In	RATED BREAKING CAPACITY ZDOLNOŚĆ ZWARCIOWA	RATED VOLTAGE NAPIĘCIE ZNAMIONOWE	CHARACTERISTIC CHATAKTERYSTYKA	PAKOWANIE PACKAGING
KFL-D02-20	23350	20A	50kA	400V AC	gG-gL	-/10/1000
KFL-D02-25	23351	25A	50kA	400V AC	gG-gL	-/10/1000
KFL-D02-35	23352	35A	50kA	400V AC	gG-gL	-/10/1000
KFL-D02-50	23353	50A	50kA	400V AC	gG-gL	-/10/1000
KFL-D02-63	23354	63A	50kA	400V AC	gG-gL	-/10/1000

